

MP-2404G

24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch



- 24x Gigabit Ethernet ports with IEEE 802.3at PoE+
- 4x 1000F(x) SFP Slot
- Built for harsh environments and wide temperature range application
- RSTP, MSTP, ERPS, LACP for Network Redundancy
- QoS CoS/DSCP to increase determinism
- Supports IGMP Snooping v1/v2/v3, up to 512 groups
- DHCP Relay Option 82 for policies IP address assignment
- SNMP v1/v2c/v3 for network management
- Supports Storm Protection
- USB storage for configuration-free replacement
- Supports industrial automation protocols Ethernet/IP and Modbus TCP
- Supports PoE PD Alive Check Function for PoE Device Power Recycle

Specifications

Technology

Standards	IEEE 802.3 10BaseT
	IEEE 802.3u 100BaseTX
	IEEE 802.3ab 1000BaseT
	IEEE 802.3z 1000BaseX
	IEEE 802.3x Flow Control
	IEEE 802.3af Power over Ethernet
	IEEE 802.3at PoE+
	IEEE 802.3az Energy-Efficient Ethernet
	IEEE 802.3ad/802.1AX LACP
	IEEE 802.1D Spanning Tree Protocol
	IEEE 802.1w Rapid STP
	IEEE 802.1s Multiple STP
	ITU-T G.8032 / Y.1344 ERPS
	IEEE 802.1Q VLAN Tagging
	IEEE 802.1ad Stacked VLANs
	IEEE 802.1p Class of Service
	IEEE 802.1X Network Authentication
	IEEE 802.1AB LLDP
	IEEE 1588 PTP

Processing Type Store and Forward

Switch Properties

Switch Fabric	56Gbps
Priority Queues	8 Queues
Jumbo Frame	9216bytes
MAC Table Size	16K
Packet Buffer	12Mbits

VLAN Table Size 4094

IGMP Group 512

ACL Group 512

Software Feature

Network Redundancy RSTP, MSTP, G.8032 ERPSv2, Port Trunking with LACP

Security 802.1X, RADIUS, TACACS+, SSL, SSH

Management IPv4, IPv6, Web, Telnet, Serial Console, CLI, SNMP v1/v2c/v3, uPnP

Diagnostics RMON, SNMP Inform/Trap, Syslog, SMTP, Port Mirroring, LLDP, RSPAN

Configuration DHCP Server/Client, Relay Option 82, TFTP, USB

Filter 802.1Q VLAN, Q-in-Q, IGMP Snooping v1/v2/v3, IGMP Querier, Independent Vlan Learning

Time Sync. NTP, IEEE1588v2 OC (Software Timestamp), TC (Hardware Timestamp)

QoS CoS, DSCP, WRR/SPQ Queuing, Storm Protection

PoE Powering Status, PoE Monitoring, Scheduling, PD Alive Check

Industrial Profiles Ethernet/IP, Modbus TCP, Profinet

Interface

RJ45 Port	24x 10/100/1000T(x) with PoE+, auto negotiation speed duplex mode, auto MDI/MDI-X
Fiber Port	4x 1000F(x) SFP Slot
PoE Pin Out	V+, V+, V-, V-, for pin 1, 2, 3, 6, Endspan, MDI Mode A
LED Indicators	Per unit: PWR1, PWR2(AC2/DC2), Fault, Ring Master, Ring State Ports: Link/Active with highest speed(Green), low speed(Amber) PoE: Output Power
Alarm Contact	1x relay output with current carrying capacity of 1A @ 24 VDC
Digital Inputs	1x isolated input from the electronics. +13 to +30V for state "1" -30 to +3V for state "0" Max. input current: 8mA
Button	Multiple functions reset button
Serial Console	1x RS232 in RJ45 connector with console cable, 115.2Kbps, 8N1
Storage	1x USB 2.0 storage for firmware update, configuration backup, restore, boot up and syslog

Power Requirements

Operation Voltage	100~240VAC, 48~57VDC, redundant dual inputs, >50VDC for PoE+ output recommended
Connection	AC socket, DC 4-pin terminal block
Power Consumption	0.38A@48VDC; 0.27A@110VAC without PDs' consumption
PoE Power Budget	Max. 348W@AC with derating (50°C to 70°C, 2.5%/°C) or 720W@DC, for total PD consumption, Max. 30 W per PoE port
Protection	Overload Current Protected, Reverse Polarity Protected

Features with star(*) implies those are under development.

In a continuing effort of improvement and updated technology, product specifications are subject to change without notice.

Mechanical Construction

Enclosure	Aluminum / Steel metal
Protection Class	IP30
Dimensions	440x44x331 mm (WxHxD)
Weight	6.00 kg
Mounting	Rack Mounting


Environmental Limits

Operating Temperature	Standard: -20°C ~ 60°C (-4°F ~ 140°F) Extended: -40°C ~ 75°C (-40°F ~ 167°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (Non-Condensing)

Regulatory Approvals

EMI	FCC Part 15 Subpart B Class A CE EN 55032 Class A
EMS	IEC61000-4-2 (ESD) IEC61000-4-3 (RS) IEC61000-4-4 (EFT) IEC61000-4-5 (Surge) IEC61000-4-6 (CS) IEC61000-4-8 (Magnetic Field)
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	UL 60950-1/62368 (Pending)
MTBF	>100,000 hours
Warranty	5 Years

Dimensions (unit = mm)



Ordering Information

MP-2404G-1AC	24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch - 24x 10/100/1000T(x) with 30W PSE + 4x 1000F(x) SFP Slot - Operating Temperature: -20°C ~ 60°C (-4°F ~ 140°F) - 1x 90~264VAC Power Input
MP-2404G-1AC-T	24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch - 24x 10/100/1000T(x) with 30W PSE + 4x 1000F(x) SFP Slot - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - 1x 90~264VAC Power Input
MP-2404G-AD	24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch - 24x 10/100/1000T(x) with 30W PSE + 4x 1000F(x) SFP Slot - Operating Temperature: -20°C ~ 60°C (-4°F ~ 140°F) - 1x 90~264VAC Power and 1x 48~57VDC Power Input
MP-2404G-AD-T	24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch - 24x 10/100/1000T(x) with 30W PSE + 4x 1000F(x) SFP Slot - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - 1x 90~264VAC Power and 1x 48~57VDC Power Input
MP-2404G-DC-T	24+4 Port Industrial Managed PoE+ Gigabit Ethernet Switch - 24x 10/100/1000T(x) with 30W PSE + 4x 1000F(x) SFP Slot - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - 2x 48~57VDC Robust Isolation Power Input