

ET-0800L-M12

8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch



- Compliant with EN50155
- 8x 10/100T(x) M12 connector with IEEE 802.3at PoE+
- Built for harsh environments and wide temperature range application
- IP40/IP54(Optional) housing
- Isolated redundant PoE power 165W



Specifications

Technology

Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3af Power over Ethernet IEEE 802.3at PoE+
------------------	--

Processing Type	Store and Forward
------------------------	-------------------

Switch Properties

Switch Fabric	1.6Gbps
----------------------	---------

Priority Queues	-
------------------------	---

MAC Table Size	8K
-----------------------	----

Packet Buffer	4Mbits
----------------------	--------

Interface

Network Connector	8x 10/100T(x) M12 Female D-coded 4-pole, auto negotiation speed duplex mode, auto MDI/MDI-X
--------------------------	---

LED Indicators	Per unit: PWR1, PWR2, Status Ports: Link/Active with highest speed(Green), low speed(Amber) PoE: Output Power
-----------------------	--

Power Requirements

Operation Voltage	9-36VDC; 19-75VDC; 43-160VDC, redundant dual inputs, >50VDC for PoE+ output recommended
--------------------------	---

Connection	M12 Male S-coded 4-pole
-------------------	-------------------------

Power Consumption	0.39A@24VDC; 0.21A@48VDC; 0.12A@110VDC
--------------------------	--

PoE Power Budget	Max. 30 W per PoE port. Max. total output power for PD: 165W@24V input (normal temp.); 60W@24V input (75°C)
-------------------------	---

Protection	Overload Current Protected, Reverse Polarity Protected
-------------------	--

Mechanical Construction

Enclosure	SECC
------------------	------

Protection Class	IP40/IP54(Optional)
-------------------------	---------------------

Dimensions	181x99x94 mm (WxHxD)
-------------------	----------------------

Weight	1.50 kg
---------------	---------

Mounting	Wall Mounting Kits, Optional DIN-Rail Mounting
-----------------	--

Environmental Limits

Operating Temperature	Extended: -40°C ~ 75°C (-40°F ~ 167°F)
------------------------------	--

Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
----------------------------	------------------------------

Ambient Relative Humidity	5 to 95%, (Non-Condensing)
----------------------------------	----------------------------

Regulatory Approvals


EMI	FCC Part 15 Subpart B Class A CE EN 55032 Class A
------------	--

EMS	IEC61000-4-2 (ESD)
	IEC61000-4-3 (RS)
	IEC61000-4-4 (EFT)
	IEC61000-4-5 (Surge)
	IEC61000-4-6 (CS)
IEC61000-4-8 (Magnetic Field)	
Free Fall	IEC60068-2-32
Shock	IEC61373
Vibration	IEC61373

Green	RoHS Compliant
Certifications	EN 50155 EN 45545-2
MTBF	>100,000 hours
Warranty	5 Years

Features with star(*) implies those are under development.
In a continuing effort of improvement and updated technology, product specifications are subject to change without notice.

Dimensions (unit = mm)



Ordering Information

ET-0800L-M12-24V2U-T	8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch - 8x 10/100T(x) with 30W PSE M12 connector - Power Input: 24VDC - Max. Power Budget: 165W - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - Protection Class: IP40
ET-0800L-M12-24V2U-WT	8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch - 8x 10/100T(x) with 30W PSE M12 connector - Power Input: 24VDC - Max. Power Budget: 165W - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - Protection Class: IP54
ET-0800L-M12-48V2U-T	8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch - 8x 10/100T(x) with 30W PSE M12 connector - Power Input: 48VDC - Max. Power Budget: 165W - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F) - Protection Class: IP40
ET-0800L-M12-48V2U-WT	8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch - 8x 10/100T(x) with 30W PSE M12 connector

- Power Input: 48VDC
 - Max. Power Budget: 165W
 - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F)
 - Protection Class: IP54
-

ET-0800L-M12-HV2U-T

- 8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch
 - 8x 10/100T(x) with 30W PSE M12 connector
 - Power Input: 72-110VDC
 - Max. Power Budget: 165W
 - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F)
 - Protection Class: IP40
-

ET-0800L-M12-HV2U-WT

- 8 Port M12 Industrial Unmanaged PoE+ Booster Ethernet Switch
- 8x 10/100T(x) with 30W PSE M12 connector
- Power Input: 72-110VDC
- Max. Power Budget: 165W
- Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F)
- Protection Class: IP54