

MP-0804X

8+4 Port Industrial Managed PoE+ Ethernet Switch with 10G Uplink



- 8x Gigabit Ethernet ports with IEEE 802.3at PoE+
- 4x 1/10 Gigabit Ethernet SFP+ Slot
- Built for harsh environments and wide temperature range application
- RSTP, MSTP, ERPS, MRP, LACP for Network Redundancy
- QoS CoS/DSCP to increase determinism
- Supports IGMP Snooping v1/v2/v3, up to 512 groups
- DHCP Relay Option 82 for policies IP address assignment
- SNMP v1/v2c/v3 for network management
- Supports Storm Protection
- USB storage for configuration-free replacement
- Supports industrial automation protocols Ethernet/IP and Modbus TCP
- Supports PoE PD Alive Check Function for PoE Device Power Recycle

Specifications

Technology

IEEE 802.3 10BaseT
IEEE 802.3u 100BaseTX
IEEE 802.3ab 1000BaseT
IEEE 802.3ae 10GBase over Fiber
IEEE 802.3x Flow Control
IEEE 802.3af Power over Ethernet
IEEE 802.3at PoE+
IEEE 802.3az Energy-Efficient Ethernet
IEEE 802.3ad/802.1AX LACP
IEEE 802.1D Spanning Tree Protocol
IEEE 802.1w Rapid STP
IEEE 802.1s Multiple STP
ITU-T G.8032 / Y.1344 ERPS
IEC 62439-2 Media Redundancy Protocol
IEEE 802.1Q VLAN Tagging
IEEE 802.1ad Stacked VLANs
IEEE 802.1p Class of Service
IEEE 802.1X Network Authentication
IEEE 802.1AB LLDP
IEEE 1588 PTP

Processing Type Store and Forward

Switch Properties

Switch Fabric 96Gbps

Priority Queues 8 Queues

Jumbo Frame 9216bytes

MAC Table Size 16K

Packet Buffer 12Mbits

VLAN Table Size 4094

IGMP Group 512

ACL Group 512

Software Feature

Network Redundancy RSTP, MSTP, G.8032 ERPSv2, IEC 62439-2 MRP, Port Trunking with LACP

Security 802.1X, RADIUS, TACACS+, SSL, SSH

Management IPv4, IPv6, Web, Telnet, Serial Console, CLI, SNMP v1/v2c/v3, uPnP

Diagnostics RMON, SNMP Inform/Trap, Syslog, SMTP, Port Mirroring, LLDP, RSPAN

Configuration DHCP Server/Client, Relay Option 82, TFTP, USB

Filter 802.1Q VLAN, Q-in-Q, IGMP Snooping v1/v2/v3, IGMP Querier, Independent Vlan Learning

Time Sync. NTP, IEEE1588v2 OC (Software Timestamp), TC (Hardware Timestamp)

QoS CoS, DSCP, WRR/SPQ Queuing, Storm Protection

PoE Powering Status, PoE Monitoring, Scheduling, PD Alive Check

Industrial Profiles	Ethernet/IP, Modbus TCP, Profinet
Interface	
RJ45 Port	8x 10/100/1000T(x) with PoE+, auto negotiation speed duplex mode, auto MDI/MDI-X
Fiber Port	4x 1/10 Gigabit Ethernet SFP+ Slot
PoE Pin Out	V+, V+, V-, V-, for pin 1, 2, 3, 6, Endspan, MDI Mode A
LED Indicators	Per unit: PWR1, PWR2, Fault, Ring Master, Ring State Ports: Link/Active with highest speed(Green), low speed(Amber) PoE: Output Power
Alarm Contact	1x relay output with current carrying capacity of 1A @ 24 VDC
Digital Inputs	1x isolated input from the electronics. +13 to +30V for state "1" -30 to +3V for state "0" Max. input current: 8mA
Button	Multiple functions reset button
Serial Console	1x RS232 in RJ45 connector with console cable, 115.2Kbps, 8N1
Storage	1x USB 2.0 storage for firmware update, configuration backup, restore, boot up and syslog

Power Requirements	
Operation Voltage	48-57VDC, redundant dual inputs, >50VDC for PoE+ output recommended
Connection	1x removable 4-contact terminal block
Power Consumption	0.32A@48VDC without PDs' consumption
PoE Power Budget	Max. 240 W for total PD consumption, Max. 30 W per PoE port
Protection	Overload Current Protected, Reverse Polarity Protected

Features with star(*) implies those are under development.


In a continuing effort of improvement and updated technology, product specifications are subject to change without notice.

Mechanical Construction	
Enclosure	Aluminum
Protection Class	IP30
Dimensions	72x145x118 mm (WxHxD)
Weight	0.90 kg
Mounting	DIN-Rail Mounting, Optional Wall Mounting Kits

Environmental Limits	
Operating Temperature	Standard: -10°C ~ 60°C (14°F ~ 140°F) Extended: -40°C ~ 75°C (-40°F ~ 167°F)
Storage Temperature	-40°C ~ 85°C (-40°F ~ 185°F)
Ambient Relative Humidity	5 to 95%, (Non-Condensing)

Regulatory Approvals	
EMI	FCC Part 15 Subpart B Class A CE EN 55032 Class A
EMS	IEC61000-4-2 (ESD) IEC61000-4-3 (RS) IEC61000-4-4 (EFT) IEC61000-4-5 (Surge) IEC61000-4-6 (CS) IEC61000-4-8 (Magnetic Field)
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	UL 60950-1/62368 (Pending) IEC 61000-6-2 IEC 61000-6-4 EN 50121-4
MTBF	>100,000 hours
Warranty	5 Years

Dimensions (unit = mm)



Ordering Information

MP-0804X	8+4 Port Industrial Managed PoE+ Ethernet Switch with 10G Uplink
	- 8x 10/100/1000T(x) with 30W PSE + 4x 1/10 Gigabit Ethernet SFP+ Slot - Operating Temperature: -10°C ~ 60°C (14°F ~ 140°F)
MP-0804X-T	8+4 Port Industrial Managed PoE+ Ethernet Switch with 10G Uplink
	- 8x 10/100/1000T(x) with 30W PSE + 4x 1/10 Gigabit Ethernet SFP+ Slot - Operating Temperature: -40°C ~ 75°C (-40°F ~ 167°F)

Optional Accessories

NDR-240-48	240W Industrial DIN-Rail Power Supply, 48VDC (metal case)
NDR-480-48	480W Industrial DIN-Rail Power Supply, 48VDC (metal case)